

MFWD SPECIFICATIONS

| | 275 | 295 | 315 | 335 | 365 |
|--------------------------------|---|-----------------------|-----------------------|-------------------------|-------------------------|
| ENGINE | | | | | |
| Engine Model | Cummins QSL9 | | | | |
| Displacement | 9 L (549 cid) | | | | |
| Horsepower ¹ | 275 hp (205kW) | 295 hp (220 kW) | 315 hp (235 kW) | 335 hp (250 kW) | 365 hp (272 kW) |
| Power Bulge | 8% @ 1,900 rpm | 8% @ 1,900 rpm | 10% @ 1,900 rpm | 10% @ 1,900 rpm | 10% @ 1,900 rpm |
| Peak Horsepower | 300 hp (216 kW) | 320 hp (239 kW) | 340 hp (254 kW) | 370 hp (276 kW) | 400 hp (298 kW) |
| PTO hp | 220 hp (164 kW) | 232 hp (173 kW) | 248 hp (185 kW) | 268 hp (200 kW) | 272 hp (203 kW) |
| Torque Rise | 45% @ 1,500 rpm | 34% @ 1,500 rpm | 29% @ 1,500 rpm | 35% @ 1,500 rpm | 31% @ 1,500 rpm |
| Peak Torque | 945 lb-ft (1,282 N•m) | 985 lb-ft (1,335 N•m) | 995 lb-ft (1,350 N•m) | 1,130 lb-ft (1,532 N•m) | 1,199 lb-ft (1,626 N•m) |
| Aspiration | Turbocharged and air-to-air aftercooled | | | | |
| TRANSMISSION | | | | | |
| Powershift Transmission | 16 forward, 9 reverse | | | | |
| Maximum Speed | 25 mph (40 km/h) | | | | |
| HYDRAULICS | | | | | |
| Type | Closed center load sensing system | | | | |
| Standard Flow | 55 gpm (208 L/min) | | | | |
| High Flow (optional) | 72 gpm (273 L/min) | | | | |
| Implement Remotes (standard) | 4 EHR | | | | |
| Implement Remotes (optional) | 6 EHR | | | | |
| Maximum System Pressure | 2900 psi (200 bar) | | | | |
| DRAWBAR | | | | | |
| Drawbar (standard) | Category III | | Category IV | | |
| Drawbar (optional) | Category IV | | - | | |
| 3-POINT HITCH & PTO | | | | | |
| 3-Point Hitch | Category III / IIIN | | Category III / IVN | | |
| PTO (standard) | 540/1,000 rpm | | 1,000 rpm | | |
| PTO (optional) | 1,000 rpm | | - | | |

MFWD SPECIFICATIONS

| | 275 | 295 | 315 | 335 | 365 |
|--|---|------------------------|------------------------|----------------------------------|------------------------|
| AXLES | | | | | |
| Front Axle (standard) | Limited slip | | | Suspended with differential lock | |
| Front Axle (optional) | Differential lock; Suspended with differential lock | | | Limited slip; differential lock | |
| CAB | | | | | |
| Volume | 149 cu. ft. (4.22 cu. m) | | | | |
| Glass | 73.5 sq. ft. (6.83 sq. m) | | | | |
| ELECTRICAL SYSTEM | | | | | |
| Alternator | 12V - 200 amps | | | | |
| Batteries | 2 12V, 950 CCA | | | | |
| FUEL SYSTEM | | | | | |
| Fuel Capacity | 165 U.S. gal (625 L) | | | | |
| DEF Capacity | 9 U.S. gal (34 L) | | | | |
| WEIGHTS & DIMENSIONS | | | | | |
| Base Tractor Weight¹ | 27,660 lbs (12,546 kg) | | | 28,060 lbs (12,728 kg) | |
| Recommended Operating GVW | 28,600 lbs (12,973 kg) | 29,762 lbs (13,500 kg) | 31,173 lbs (14,140 kg) | 33,950 lbs (15,400 kg) | 35,400 lbs (16,057 kg) |
| Wheelbase | 124.6" (3,165 mm) | | | 128.95" (3,275 mm) | |

¹SAE horsepower measured @ 2,100 rpm

²Estimated weight based on standard drawbar, no fuel, no operator, no ballast, no additional equipment

NOTE: Specification are correct at time of publishing and are subject to change