



# SELF-LEVELING LOADER

» Model 3995E



» Model 3995E

SELF-LEVELING LOADER



# SPECIFICATIONS » 3995E

3995 LOADER SPECIFICATIONS	3995 SLS STANDARD STEER	3995 SL ULTRASTEER
Loader - type	Mechanical true self-leveling system complete with manifold and block relief valve	
Breakout force	9,950 lb-ft at pivot pin	8,811 lb-ft at pivot pin
Maximum lift capacity	6,875 lb (3125 kg)	6,989 lb (3170 kg)
Lift cylinders	3.5 in (90 mm) diameter, 35 in (889 mm) stroke, 2.0 in (51 mm) shaft	
Bucket cylinders	3.0 in (76 mm) diameter, 21 in (533 mm) stroke, 1.75 in (44 mm) shaft	
Maximum lift height	169 in (4.3 m) to pivot pin	187 in (4.75 m) to pivot pin
Maximum dump angle	61°	59°
Maximum rollback angle	35°	45°
Cushion ride kit	Absorbs abrupt forces caused by suddenly dropping a heavy load or when driving across rough ground.	

OPTIONAL ACCESSORIES FOR THE VERSATILE 3995 SL LOADER	
<b>Quick-tach buckets</b>	
100S in (3.78 m), multi-purpose	1.20 cu. yd. capacity, prepunched for grapple tines
100H in (4.02 m), multi-purpose	1.65 cu. yd. capacity, prepunched for grapple tines
96 in (3.78 m), snow	2.25 cu. yd. capacity
85 in (3.35 m), manure	1.20 cu. yd. capacity, complete with 36 in (0.9 m) tines
<b>Bucket tines</b>	
For 96 in and 102 in bucket	Bolt on 21 in (0.52 m), quantity of 10
<b>Grapples</b>	
For 85 in, 96 in and 102 in bucket	84 in cross tube with 5 adjustable grapple weldments
For 100H in bucket	Model 3000 - handles 6 ft diameter and larger round bales, 84 in cross tube, with 5 adjustable grapple weldments
<b>A-frame</b>	
Stabilizers - standard	2
Attachments	Accepts bale spears and pallet forks
<b>Bale spears</b>	
49 in (1.24 m)	1, 2 or 3 spears
<b>Pallet fork kit</b>	
Tine dimensions	48 in (1.22 m) long x 1.5 in (38 mm) thick x 4 in (102 mm) wide
Weight capacity	4,400 lb (2000 kg)
Amount of adjustment on shaft	11.25 in (280 mm)

JOYSTICK OPTIONS	MECHANICAL	ELECTRONIC
Location	Cab right hand console	Cab right hand console
Circuits	Two or three circuit. Three circuit valve has separate grapple function with thumb controlled rocker switch.	Three circuit for grapple operation. In console options for tractors equipped with shuttle shift.
Float function	On the loader lift circuit	On the loader lift circuit

All 3995 SL Loaders come with standard color coded hookup quick attach system, parking stand, hydraulic lift lock, bucket level indicator and grill guard.



Equipment shown is subject to change without notice.